

WEFLO®



WEFLO
FIRE MAIN GATE VALVE
FIG. F0211-300
UL LISTED
3NEA
VALVE COMPANY LTD.

1 OS&Y

DN 65 – DN300
 : 20,7 (300 psi).
 AWWA C515. (FBE)
 AWWA C550. EPDM.
 : FM/UL

2 NRS

DN 65 – DN300
 : 20,7 (300 psi).
 C515. (FBE) AWWA C550.
 EPDM.
 : FM/UL

3

? ”
 : FM/UL

4

? ”
 : FM/UL

5 ()

DN 50 – Dn300
 : 20,7 (300 psi).
 AWWA C508.
 EPDM
 (FBE) AWWA
 C550.
 : FM/UL

6 NRS

DN 65 – DN300
 : 20,7 (300 psi).
 C515. (FBE) AWWA C550.
 EPDM.
 : FM/UL

7 NRS (MJ)

DN 80 – DN300
 : 20,7 (300 psi).
 C153/A21.53. ANSI/AWWA
 AWWA C515. (FBE)
 AWWA C550. EPDM.
 : FM/UL



8 ()
 DN 65 – DN300 : 20,7 (300 psi).
 AWWA C606.
 EPDM (FBE) AWWA
 C550.
 : FM/UL

9
 DN 50 – DN300 : 20,7 (300 psi).
 AWWA C606.
 (FBE) AWWA
 C550.
 EPDM.
 : FM/UL

10
 DN 50 – DN300 : 20,7 (300 psi).
 ANSI B16.1 125,
 EN1092-2 PN10/16.
 (FBE) AWWA C550. EPDM.
 : FM/UL

11
 DN 50 – DN300 : 16 (230 psi).
 EN1092-2 PN16/25, ANSI B16.1
 125, AISI 304 (FBE)
 EPDM/NBR.

12
 DN 50 – DN300 : 16 (230 psi).
 ANSI/AWWA C606.
 (FBE). EPDM.
 ISO5211-1.

13
 DN 80 – Dn200 : 20,7 (300 psi).
 ANSI B16.1 125, EN1092-2
 PN10/16 AWWA C606.
 (FBE).
 : UL,

14
 DN 40 – DN300 : 20,7 (300 psi).
 ANSI B16.1 125, EN1092-2
 PN10/16, AWWA C606.
 (FBE).
 :

15
 DN 40 – DN300 : 20,7 (300 psi).
 ANSI B16.1 125, EN1092-2
 PN10/16, AWWA C606.
 (FBE).
 :

16
 DN150 : 17,2 (250 psi)
 AWWA C502. (FBE)
 AWWA C550.
 (4,5") (2,5").
 : FM/UL



WEFLO®

Weilong Valve Co. Ltd.

1992

2015

65 000 2

WEFLO.

900

WEFLO

ISO 9001:2008

ped (PED)

I, II III,

PN6, PN10, PN16, PN25 PN 40.

UL (Underwriters Laboratories) FM

(Factory Mutual).

NORMBUD

ARMATURA ■ TECHNIKA PRZECIWPO ■ AROWA ■ ELIWO

04-987 Warszawa; ul. Wał Miedzeszy ski 177K
tel: (22) 761-10-12; fax: (22) 781-96-51
www.normbud.pl